

EECE.2160: ECE Application Programming

Summer 2018

Lecture 12: Key Questions

June 21, 2018

QUESTIONS:

1. Explain the use of the `fopen()` function.
2. Explain the use of the `fclose()` function.
3. Explain how `fscanf()` and `fprintf()` are used for formatted file I/O.
4. Explain how `fread()` and `fwrite()` are used for unformatted I/O.
5. Describe the standard input and output streams.
6. Describe how to test that an operation has reached the end of a file or caused an error.
7. Describe the functions used for character I/O.
8. Describe the functions used for line I/O.

EXAMPLES:

1. Write a program to:
 - Read three integers from file `myinput.txt`
 - Determine the sum and average of those values
 - Write the original values, sum, and average to file `myoutput.txt`.

2. Show the output of each of the following short program.

a. Input: **Test Input** **1** **23 4 5**

```
void main() {
    char c;
    char buffer[50];
    int i, n;
    i = 0;
    while ((c = fgetc(stdin)) != '\n') {
        if (c != ' ') {
            buffer[i++] = c;
        }
    }
    buffer[i] = '\0';
    fputs(buffer, stdout);
}
```

b. Input:

Test1

Test 2

abcdefghijklmnopqrstuvwxy

This is a test of the fgets() function

```
void main() {
    char str[25];
    int i;
    for (i = 0; i < 5; i++) {
        fgets(str, 24, stdin);
        strcat(str, "\n");
        fputs(str, stdout);
    }
}
```

c. Input:

1024Some other stuff

```
void main() {
    char c;
    char buffer[50];
    int n = 0;

    // isdigit in <ctype.h>
    while (isdigit(c = getchar())) {
        n = n * 10 + (c - 48);    // Hint: '0' = 48    }
        // (ASCII value)
    ungetc(c, stdin);
    fgets(buffer, 50, stdin);

    printf("n = %d, n * 2 = %d\n", n, n * 2);
    printf("buffer = %s\n", buffer);
}
```